

# Russell Timber Technology Data Sheet

## Conservation Timber Entrance Doors

### High Performance & Energy Efficient

#### Overview

Hardwood Entrance Doors are traditionally used in Conservation properties, combining classic looks with top performing security and energy efficiency.

Russell Timber Tech **Secured by Design** and Energy Efficient Entrance Doors achieve **U-Values to 1.1 W/m2K**.

These doors are suitable for use with most **QTE 7** and **QTE 8** designs.

Various screen, fanlight and sidelight combinations are available. Glazing specification can be varied to suit the location and usage.



Our product range can be supplied fully factory finished from a selection of stains and colours. The colours shown are for illustration only. Please check RAL/BS numbers. Other RAL/BS colours can be supplied which, dependant on quantity, may attract an additional charge.



Oxford Blue  
BS 20D45



Pine Green  
RAL 6028



Steel Grey  
RAL 7011



Light Oak  
Stain



Mahogany  
NCS 8010-Y90R



Midnight Blue  
BS 20C40



Teak  
Stain



White  
NSC S0502Y



Wine Red  
RAL 3003

### Secured by Design



### Police Preferred Specification



The mark of  
responsible forestry



All products and production are subject to continuous development. The company reserves the right to amend details and sizes without notice.

John A Russell (Joinery) Ltd

8 Dilwara Avenue, Glasgow, G14 0QS

Telephone: 0141 958 0444 | Fax: 0141 958 0333 | Website: [www.russelltimbertech.co.uk](http://www.russelltimbertech.co.uk)

Company Registration: SC045289 | VAT No: 260 8552 57 | Data Sheet Ref: PDS 006-01 / 14.04.14

**RUSSELL**

**Timber Technology**

Engineered to excel

# Russell Timber Technology Data Sheet

## Conservation Timber Entrance Doors

High Performance & Energy Efficient

### Styles

Designs with multi-glazing units (7.10G, 7.16G, 7.17G, 7.18G, 7.20G, 7.22G, 8.7G, 8.8G, 8.9G, 8.15G) are quoted with bronze glazing bars within the glass except products finished in white, which will have white glazing bars within the glass. Timber astragals complete with back-to-back spacer are available.



# Russell Timber Technology Data Sheet

## Conservation Timber Entrance Doors

High Performance & Energy Efficient

### Styles

Designs with multi-glazing units (7.10G, 7.16G, 7.17G, 7.18G, 7.20G, 7.22G, 8.7G, 8.8G, 8.9G, 8.15G) are quoted with bronze glazing bars within the glass except products finished in white, which will have white glazing bars within the glass. Timber astragals complete with back-to-back spacer are available.

